

P5 SMD LED Downlight

Description:

P5 downlights made by Opte Lighting have been specifically designed to produce a cost effective and well performing downlight solution to the market. LED recessed downlight with an anti-glare PMMA Cover, complete with a high quality LED driver ,it produce a wide spread of uniform light ,a comfortable and Very homogenous light.

It is Ideal for for your planned retrofit or new constructing, Creating tremendous energy saving at a extremely affordable price



Application:

- General Lighting areas
- Hotel Office Lighting
- Residential Lighting
- Retail Shop





































Zhongshan Factory: No. 50, Shengyu 1st Street, Henglan Town, Zhongshan City, Guangdong Province



Information:

Features:

- Opal diffuser glare free design ,Spread a very homogenous light
- Direct replacement for compact fluorescent lamp downlights
- Energy savings of up to 60 % compared to luminaires that use CFL
- Adopt aluminum alloy as material die-casting process, high-end and gorgeous
- Low UGR < 19
- High transmission PMMA Cover
- No UV or IR radiation
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C
- Working environment temperature: -20oc ~ +45oc.
- Dimming options : Triac 0/1-10V DALI













Model Number	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	сст (к)	CRI	Size (mm)	Cutout(mm)
OP-DLP9W P5	AC220V-240V	9W	OSRAM	900LM	100	2700K 3000K 4000K 5000K 6000K	80+	9W	9W
OP-DLP15W P5	AC220V-240V	15W	OSRAM	1500LM	100	2700K 3000K 4000K 5000K 6000K	80+	15W	15W
OP-DLP18W P5	AC220V-240V	18W	OSRAM	1800LM	100	2700K 3000K 4000K 5000K 6000K	80+	18W	18W
OP-DLP25W P5	AC220V-240V	25W	OSRAM	2600LM	100	2700K 3000K 4000K 5000K 6000K	80+	25W	25W
OP-DLP30W P5	AC220V-240V	30W	OSRAM	3000LM	100	2700K 3000K 4000K 5000K 6000K	80+	30W	30W
OP-DLP35W P5	AC220V-240V	35W	OSRAM	3500LM	100	2700K 3000K 4000K 5000K 6000K	80+	35W	35W



