

## TLF Integrated LED Track Light

### Description:

TLF Track Light originally researched and developed by OPTE, high-end spotlight with PHILIPS Integrated driver and Bridgelux COB, With Simple and elegant design cold forging aluminum body with excellent heat dissipation, Advanced design of ultra-thin hybrid optical lens, with first-rate lighting control effect, various beam angle 15°, 24°, 38°, 60° for option, stable specifications, glare-free, brilliant quality, more than 50,000 hours life span.

It is Ideal for for your planned retrofit or new constructing, Creating tremendous energy saving at a extremely affordable price

### Application:

- Shopping mall, jewelry shop and fashion store lighting.
- Gallery, furniture, hardware, museum and showroom lighting .
- Gym, hotel and stage lighting.
- Food Lighting ( Meat Fruit Vegetable Bread etc.)



## Information:

### Features:

- SDCM=3
- Class 2
- UGR less than 19
- Flicker Free
- No UV or IR radiation
- Flexible beam direction adjustable: 355° horizontally and 90° vertically.
- Strongly light up an object from far or high distance.
- Medium useful life > 50,000 hours (L80B50) at ambient temperature of 25 °C

### Specification:

- Power supply : PHILIPS / ALLOOKING
- LED COB : Bridgelux
- Track adapter: 2 wires 3 wires 4 wires
- Housing material: aluminum.
- Housing color: White, Black
- Working environment temperature: -20oc ~ +45oc.
- Lamp Certificates: CE ROHS SAA
- Driver Certificates : TUV CB UL CE ROHS SAA

Model No.	Input voltage(V)	Power (w)	LED Chip	Luminous flux (lm) (±5%)	Beam angle(o)	CCT (K)	CRI	Size (mm)
OP-TLF25W (IG)	AC220-240V	25W	Bridgelux	3200LM	15, 24, 38,60	2700K 3000K 4000K 5000K	90+	D72 H123mm
OP-TLF30W (IG)	AC220-240V	30W	Bridgelux	3900LM	15, 24, 38,60	2700K 3000K 4000K 5000K	90+	D80 H131mm
OP-TLF35W (IG)	AC220-240V	35W	Bridgelux	4500LM	15, 24, 38,60	2700K 3000K 4000K 5000K	90+	D90 H141mm
OP-TLF40W (IG)	AC220-240V	40W	Bridgelux	5200LM	15, 24, 38,60	2700K 3000K 4000K 5000K	90+	D100 H141mm

## Dimension :

